

Volvo Articulated Haulers 55 t 639 hp

A60H



Being the first. Keeping the lead.

Since introducing Gravel Charlie, the world's first series manufactured articulated hauler, Volvo has consistently led the way when it comes to pioneering technology which delivers the ultimate in sustainable productivity and performance. Today we offer the most comprehensive range of articulated haulers in the industry, with common technology throughout, ensuring optimum results whatever size class you are operating. Combine this with a range of complementary services and solutions and Volvo Articulated Haulers deliver the lowest possible cost per tonne.

1966

1967

19/3

1993

A40

2000

DR631 "Gravel Charlie"

The world's first series manufactured articulated hauler DR 860

3-axle machine with unique bogie concept 5350

Featuring fully automatic transmission, unique suspension system and class leading cab with low noise level A25C


The first articulated hauler with low emission engine as standard Product range from

20t to 40t

D-seriesBuilt with
a focus
on the
operator



As part of our enduring focus on environmental care we are committed to Science Based Targets (SBTi) to achieve net-zero value chain emissions by 2040, with significant emission reductions as early as 2030. From product planning, manufacturing and supply, through to end-of-life, our focus continues to be on minimizing our global footprint and driving transformation in our industry.



2007

E-series and A40 FS

The world's first full suspension articulated hauler

2011

F-seriesFurther improving ease of operation and environmental care

2014

G-seriesWet, cooled
brakes on all
models

2016

A60H The world's largest articulated hauler TODAY

A 25t to 55t product offering, complete with a range of services

Keep on moving

Effective maintenance can have a big influence on your total cost of ownership. Volvo Articulated Haulers are designed to be easy to service, helping you to maximize your uptime and keep maintenance costs to a minimum.

Reduce oil volume by half

When measured over the lifetime of the machine, Volvo Articulated Haulers require less than half the fluid volume compared to competition, benefitting both the environment and your operating costs.



Easy to service

Servicing your machine is quick and easy thanks to industry leading service access and essential maintenance points accessible from the ground. The front grill swings down, opening a service platform with anti-slip steps and the electric hood opens to 90 degrees, allowing full access to the engine compartment.



Service alerts

Fluid levels are constantly monitored with timely service alerts displayed on the dashboard, helping you stay on top of your maintenance requirements.





NO DAILY OR WEEKLY GREASING

With Volvo Articulated Haulers greasing is only required every 250 hours – the best in the industry – delivering maximum uptime.

Haul Assist

Gain access to a set of tools designed to help you get the most out of your Volvo Articulated Hauler and boost your profitability.

Proactive tire management

Optimize tire life with the support of the Tire Pressure Monitoring System, which allows the operator to monitor tire pressure and temperature from the comfort of the cab.



A complete site overview

Monitor the whereabouts of all your machines, vehicles and visitors in real-time with Map, a connected tool which provides accurate positioning to help monitor on-site traffic and navigate the site more efficiently.



Go into detail

Reports can be generated automatically on a daily and weekly basis, or manually at any time, including the geo-tracking of moved material which is enabled by Map.



Support you can count on

As a fully integrated and factory-fitted Volvo system, all the components, hardware and software of Haul Assist are supported by your Volvo dealer to keep your operation running smoothly. What's more, you will benefit from over-the-air updates, easy upgrades and remote support.





TAKE CONTROL OF YOUR PRODUCTIVITY

On-Board Weighing provides real-time payload information which can help to eliminate carry-back and overloading; the result is peak productivity, reduced fuel consumption and less machine wear.

Bigger and bolder

With 100% off-road performance, proven Volvo technology and impressive payload, count on the Volvo A60H Articulated Hauler to boost your profits.

Comfort at speed

The A60H is fitted with active hydraulic front suspension – permitting high hauling speeds in tough conditions. This optimizes operator comfort and stability during travel.



Unbeatable off-road performance

The ground-breaking A60H is the best articulated hauler on the market. With matched drivetrain, automatic drive combinations including 100% differential locks, all-terrain bogie and hydromechanical steering, this machine is unbeatable.



Articulated hauler concept

Go where others can't. The A60H embodies the full articulated hauler concept and provides total versatility so you can access the entire jobsite and climb steeper gradients. Work in all seasons, terrains and applications using tailored machine configurations and tires, optimized for this 60 tonne machine.





MOVE MORE FOR LESS

Reach your production targets faster and reduce your cost per tonne with the Volvo A60H. The largest articulated hauler on the market offers up to 40% more productivity along with outstanding fuel efficiency.

Control in comfort

The industry-leading cab appeals to operators and helps maintain productivity all day, every day.

Total control

Stay in control at all times. The dump support system, dynamic Volvo engine brake, load and dump brake and hill assist, all help the operator to control the machine for extra productivity and safety.



Ease of operation

The ergonomic, comfortable and easy-to-understand controls are designed to suit all operators, combined with automatic functions for increased ease of operation.



Operator comfort

Feel comfortable and spend more time in the Volvo Articulated Haulers. The centrally positioned operator, superior steering, excellent suspension, low noise levels, climate control, space and visibility reduce operator fatigue for more effective operations.



Safety first

Whether its operators, trainers, technicians or site workers – safety on site is of fundamental importance. In the Volvo Articulated Haulers superior visibility and efficient lighting combine with features such as the brake test and dump support, helping to keep everyone working around the machine safe.





OPERATOR'S CHOICE

A happy operator is a more productive operator and when many other machines are onsite, most operators prefer the Volvo. Even in the most adverse conditions, its comfortable cab and ease of operation keep operators alert and performing their best.

Simply the best and the biggest

Only from Volvo

- Proven Volvo engine and matched driveline: high performance, high fuel efficiency
- Automatic drive combinations including 100% differential locks, all-terrain bogie and hydromechanical steering
- Active hydraulic front suspension for high hauling speeds in tough conditions
- The largest articulated hauler on the market, delivering 40% more productivity

The operator's choice

- Ease of operation: ergonomic and easy-to-understand controls
- Centrally positioned operator for best-in-class visibility
- Hill assist, dump support system, load and dump brake
- Built-in brake test: schedule and perform a stationary brake test, guided by the machine display

Solutions for you

- Easy machine monitoring: CareTrack, ActiveCare
- Genuine Volvo Parts
- Volvo Site Simulation: get recommendations on the best fleet configuration and site set-up
- Operator Training Program: unlock the full potential of your machine
- Uptime Services: control your maintenance costs



Haul Assist

- On-Board Weighing: real-time payload monitoring
- Tire Pressure Monitoring System
- Map: real-time positioning of on-site traffic
- Productivity Reports, including the geo-tracking of moved material
- Over-the-air updates, easy upgrades, remote support

Service and maintenance

- 250-hour greasing interval
- Half the fluid volume compared to the competition
- Service reminders and fluid level monitoring
- Industry-leading service access and groundaccessible service points



Configured for success

Ensuring your fleet is configured in the correct way can yield huge benefits to your operation including more productivity, enhanced performance and less costs.

Here are some tips to help tailor your new Volvo Articulated Hauler according to the application, site conditions and type of transported material, as well as matching to the appropriate loading unit. For more detailed information, talk to your Volvo dealer!

Body options

Question	Answer	Solution
Dealing with height restrictions?	No	Select standard body
Operating in restricted height conditions e.g. silos or underground	Yes	Select low profile body
Hauling about its material	No	Go to next question
Hauling abrasive material? Granite, silicate etc	Yes	Select wear plates / rock liners for extended service life
	> 1.5 ton/m³ (gravel, blasted rock)	Go to next question
What material density? Gravel is ~1.65 ton/m³	1.1 - 1.5 ton/m³ (dry earth, shale)	Select side extensions to increase body volume
	< 1.0 ton/m³ (coal, fly ash etc)	Select light material kit to increase body volume
Front spill protection needed?	No	Go to next question
Getting loaded by large excavator	Yes	Select front spillguard
	No	Go to next question
Extra load retention needed? Risk of dropping material e.g. when climbing	Yes, but not hauling boulders	Select tailgate – overhung type – to reduce spillage
steep inclines	Yes, hauling boulders	Select tailgate – underhung type – to reduce spillage
Hauling sticky material?	No	Go to next question
Risk of carry-back	Yes	Select body exhaust heating

Exceeding gross machine weight is not permitted. Payload should be reduced by the weight of the optional equipment.

Tires

Question	Answer	Solution
Operating on abrasive haulroad?	No	E3 tires are optimized for soft ground, offering the best traction and high average speed
Risk of tire cuts or extensive wear	Yes	Select E4 tires for the best cut resistance, comfort and tread life
	No	Select standard profile tires
Extra flotation needed? Risk of sinkage in soft ground	Yes	Select low profile tires, featuring lower ground pressure for improved flotation, stability and comfort



Optimal pass-matching

Volvo	EC480	EC530	EC550	EC750	EC950
Excavator		Nu	mber of pas	ses	
A60H	11	9	8	7	5

	Excavator overcapacity, 3 buckets or below
	Well matched, 4-6 buckets (≈ 90 seconds loading time)
	Excavator undercapacity, 7 buckets or more
	Excavator undersized for optimum match

Volvo	L220 L260 L350					
Wheel Loader	Number of passes					
A60H	6	5	4			

Loader overcapacity, 2 buckets or below
Well matched, 2-3 buckets (≈ 90 seconds loading time)
Loader undercapacity, 4 buckets or more
Loader undersized for optimum match. Reach might also be an issue



Hauler chassis solutions

With Special Application Solutions and different chassis options you can tailor Volvo Articulated Haulers to your specific needs.



Volvo A60H in detail

Engine

16 liter, 6-cylinder straight turbocharged diesel engine with 4 valves per cylinder, overhead camshaft and electronically controlled unit injectors. The engine has wet replaceable cylinder liners and replaceable valve guides and valve seats.

Engine model	Volvo	D16F
Max power - SAE J1995 Gross	kW	495
	hp	673
at engine speed	r/min	1800
Flywheel power - ISO 9249, SAE J1349 Net	kW	492
	hp	669
at engine speed	r/min	1800
Max torque - SAE J1995 Gross	Nm	3 200
Max torque - ISO 9249, SAE J1349 Net	Nm	3 177
at engine speed	r/min	1 050
Displacement	1	16.1

Electrical System

All cables, sockets and pins are identified. Cables are enclosed in plastic conduits and secured to main frame. Halogen lights. Prewired for options. Connectors meet IP67 standard for water-proofing as necessary.

Voltage	V	24
Battery	V	2x12
Battery capacity	Ah	2x225
Alternator	kW/A	2.264/80
Starter motor	kW	9

Drivetrain

Torque converter with built-in lock-up function.

Transmission: Fully automatic Allison planetary transmission with 6 forward gears and 2 reverse gears. Internal torsional damper in the torque

Dropbox: Volvo-developed, in-line design with high ground clearance and 100% longitudinal "dog clutch" type differential lock. **Axles:** Heavy duty, purpose built Volvo design with fully floating axle shafts, planetary type hub reductions and 100% dog clutch type diff-lock. Automatic traction control system (ATC).

Torque converter		1.85:1
Transmission	Volvo	6630 ORS
Dropbox	Volvo	IL3 ATC
Axles	Volvo	AHW80

Brake system

Fully hydraulic, wet multiple disc brakes with enclosed, forced oil-cooled multiple discs on all wheels. Two circuit brake system. Complies with ISO 3450 at total machine weight.

Circuit division: One circuit for front axle and one for bogie axles.

Parking brake: Spring-applied disc brake on the propeller shaft, designed to hold a loaded machine on a grade of up to 18%. When the parking brake is applied, the longitudal differential is locked.

Retarder: Service brake retarder function and Volvo Engine Brake (VEB).

Steering System

Hydro-mechanical articulated steering, self compensating design.

Two double-acting steering cylinders. **Steering angle:** 3,4 steering wheel turns lock-to-lock, ±45° Steering system, including secondary steering fulfi lls ISO 5010.

Frames: box type, heavy duty. High strength steel, robot welded.
Rotating hitch: 100% maintenance free, fully sealed, with permanently greased tapered roller bearings.

Cab

Mounted on rubber pads. Ergonomically designed. Easy entry and exit. Wide angle forward view.

Operator centerally positioned above the front axle. Adjustable operators seat with retractable seat belt.

Tilt/telescopic steering wheel. Ergonomically positioned controls. Filtered air. Climate control system.

Operator communication system: Contronics.

Large color display, user-friendly and easy-to-understand information, all vital machine functions are constantly monitored.

Instructor seat with seat belt.

Safety: ROPS/FOPS standards approved according to ISO3471, SAE J1040 / ISO3449, SAE J231.

Sound level in cab (ISO 6396) - L _{pA}	dB	72
External sound level (ISO 6395) - LWA	dB	113

External sound level with sound kit: 111 dB(A)





Hydraulic system

Tensile strength

Pumps: Five variable displacement piston pumps driven by the flywheel PTO.

One ground-dependent piston pump for secondary steering mounted on the dropbox.

Two return oil fi lters with magnetic cores provide effective oil filtration.			
System max working pressure	MPa	28	
Dumping System			
Patented Load and Dump Brake. Dumping Cylinders: two single stage do	uble acting cylinde	ers.	
Tipping angle	0	70	
Tipping time with load	s	13	
Lowering time	s	10	
Body			
Plate thickness			
Front	mm	8	
Sides	mm	14	
Bottom	mm	16	
Chute	mm	16	
Material		HB400 steel	
Yield strength	N/mm²	1000	

N/mm²

1 250

Load Capacity		
Standard Body		
Load capacity	kg	55 000
Body, struck	m³	25.8
Body, heaped 2:1	m³	33.6
With overhung tailgate		
Body, struck	m³	26.5
Body, heaped 2:1	m³	35.1

Suspension

Front suspension: Unique, full hydraulic, with automatic leveling and stabilizer.

Rear suspension: 100% maintenance free. Straddle mounted bogie beam. Independent wheel movement via a 3-point mounting system.

Hydraulic cylinders (struts), front/rear	2/0
Accumulators, oil-nitrogen, high pressure, front	2
Levelling sensors	2



Specifications

REFILL CAPACITIES		
Crankcase	I	55
Fuel tank	1	750
Cooling system	- 1	75
Brake cooling system	I	131
Transmission	- 1	58
Dropbox	1	12
Axles, front/bogie	- 1	74/147
Hydraulic tank	1	198

SPEED		
Forward		
1	km/h	7
2	km/h	10
3	km/h	13
4	km/h	19
5	km/h	26
6	km/h	55
Reverse		
1	km/h	5
2	km/h	8

OPERATING WEIGHT UNLOADED		
Tires		33.25R29
Front	kg	22 350
Rear	kg	21 050
Total	kg	43 400
Payload	kg	55 000


Front	kg	22 350	Front
Rear	kg	21 050	Rear
Total	kg	43 400	Total
Payload	kg	55 000	

Operating weight includes all fluids and operator

GROUND PRESSI	GROUND PRESSURE				
Tires		33.25R29			
Unloaded					
Front	kPa	125			
Rear	kPa	58			
Loaded					
Front	kPa	159			
Rear	kPa	193			

TOTAL WEIGHT

Tires



DIMENSIONS				
Pos	Unit	A60H		
Α	mm	12 225		
A ₁	mm	5 872		
A ₂	mm	6 900		
В	mm	6 310		
С	mm	3 852		
C ₁	mm	1 772		
D	mm	3 293		
D ₁	mm	2 986		
E	mm	1 440		
F	mm	5 050		
G	mm	2 140		
Н	mm	1 743		
1	mm	541		
J	mm	3 510		
K	mm	2 658		
L	mm	1 030		
M	mm	7 960		
N	mm	10 014		
N ₁	mm	4 761		
0	mm	3 989		

DIMENSIONS		
Pos	Unit	A60H
Р	mm	3 673
Q	mm	3 370
R	mm	677
R ₁	mm	778
S	mm	3 126
Т	mm	3 734
U	mm	3 833
V	mm	3 010
W	mm	3 884
Χ	mm	601
X ₁	mm	727
X_2	mm	845
Υ	mm	3 010
Z	mm	3 884
a ₁	0	24.9
a ₂	0	70
a ₃	0	45

A60H: Unloaded machine with 33.25R29 tires.

Equipment

STANDARD EQUIPMENT

Engine

Direct injected, electronically controlled, turbocharged, intercooled

Grouped oil filters

Preheater for easier cold starts

VEB (exhaust retarder EPG + compression brake)

Tires

33.25R29

800/80R29

Drivetrain

6x4 and 6x6 automatically engaged drive modes

Dog clutch type 100% diff-locks in all axles

Full automatic transmission

Two-stage dropbox with longitudinal diff-lock

Torque converter with automatic lock-up

Electrical System

80 A alternator

Battery disconnect switch

Extra 24 V socket for lunch cooler

Lights:

Back-up light

Brake lights

Cab lighting

Direction indicators

Headlights

Instrument lighting

Parking lights

Rear lights

Brake system

Hill assist

Load & Dump Brake

Retarder pedal

Parking brake on propeller shaft

Two circuit, fully hydraulic, wet discs on all axles

Body

Body prepared for exhaust heating and optional equipment

On board weighing (OBW)

Safety

Anti-slip steps and platforms

Dump body lock

Handrails on steps and platforms

Hazard lights

Horn

Protective grill for cab rear window

Rear-view mirrors

Retractable 3-inch safety belt

ROPS/FOPS - certified cab

Secondary steering

Steering joint lock

Windshield washers

Windshield wipers with interval function

Dump support system

STANDARD EQUIPMENT

Comfort

ACC control panel

Ashtray

Cab heater with filtered fresh air and defroster

Can holder/storage tray

Cigarette lighter

Instructor seat with seat belt

Overhead console for radio

Sliding window

Space for lunch cooler

Storage box

Sun visor

Tilt/telescopic steering wheel

Tinted glass

Operator information interface

Gauges:

Brake pressure

Fuel

Speedometer

Tachometer

Wet disc brakes cooling oil temperature

Warning lights grouped and easy to read

Central warning (3 levels) for all vital functions

Central positioned information display

Automatic pre-start checks

Clock

Hour meter

Operational information, easy-to-navigate menu

Troubleshooting diagnostics

Exterior

Front mudguard wideners and rear mudflups

Service and maintenance

Electrical engine hood and belly plate

Drainage hose

Machine Tracking Information System MATRIS

Service platform integrated in the front $\mbox{\it grill}$

Tool box

OPTIONAL EQUIPMENT

Engine

Air pre-cleaner, cyclone type

Air pre-cleaner, oil-bath type

Air filter, heavy duty, EON

Engine heater, 240 V

Engine heater, diesel (Eberspächer)

Engine auto shutdown

Engine shutdown timer

External emergency engine stop

Fuel filter, extra

High engine idle speed

OPTIONAL EQUIPMENT

Electrical System

Headlights, LED

Warning beacon, LED

Working lights, LED

Entrance light

Seat belt indicator, external

Anti-theft system (pin code)

Rear view camera

Reverse alarm

CAN-BUS interface, extra

Cab

Noise reduction kit (fulfils 2000/14/EC)

Anchorage, operator's manual

Cab heating/ventilation timer

Cable kit, for cab heater

HEPA cab air filter

Bluetooth radio kit

Rear view mirrors, adjustable, el.heated

Seat belt XXL, non-retractable

Sun blinds, side windows

Universal key

Air suspended, heated, fully adjustable seat

Armrest for operator seat

Headrest for operator seat

Air blow gun

OPTIONAL EQUIPMENT

Body

Body exhaust heating

Front spillguard, extra

Side extension, light material

Tailgate, overhung, wire-operated

Wear plates

Safety

Fire suppression system

Warning triangle

First aid kit and fire extinguisher

Fire extinguisher

Wheel chocks

Service and maintenance

Lube system, standard machine

Tool kit

Other

Siberian kit -40°C

Arctic oil kit

CareTrack

Fast fuelling system

Jump start connector, NATO -type

Haul Assist - Tire Pressure Monitoring System

Hauler chassi (without body)


SELECTION OF VOLVO OPTIONAL EQUIPMENT

Fire suppression system

Wheel chocks



Fast fuelling





Hauler chassis





LED lighting

Auto lube



Not all products are available in all markets. Under our policy of continuous improvement, we reserve the right to change specifications and design without prior notice. The illustrations do not necessarily show the standard version of the machine.

Solutions for you

Our industry leading machines are just the start of your relationship with Volvo. As your partner, we have developed an extensive range of additional solutions to help you improve uptime, boost productivity and reduce costs.

Our portfolio of products and services is designed to complement your machine's performance and boost your profitability. Simply put, we offer some of the best guarantees, warranties and technological solutions in the industry today. Below are just some examples.

Talk to your dealer to find out and discuss the right fit for you!



Get the most from your machine

While reliable and efficient machines of course play a vital role in reducing costs, enhancing safety and maximizing productivity, it is ultimately the performance of the operator that really makes the difference. We offer a range of training initiatives to help operators unlock the full capability of their Volvo Articulated Hauler.

Connected to Uptime

Maximize machine uptime and reduce repair costs with the CareTrack telematic system. Choose to keep track of your machine yourself or let us take care of it with ActiveCare. Our Volvo Uptime Center will provide 24/7 machine monitoring, supplying weekly reports and notifying you should preventive maintenance action be required.



Control your maintenance costs

Stay on track with planned servicing and keep your asset covered with our range of flexible maintenance and repair agreements.

Optimize site efficiency

Using Volvo Site Simulation, we can help you make on-site logistics more efficient and lower your cost per tonne. Get recommendations on the best fleet configuration and site set-up to maximize profitability.

Genuine Volvo Parts

Maintain productivity and machine uptime with our range of readily available, tested and approved parts – all backed by Volvo warranty. Only by using Genuine Volvo Parts, can you protect your investment, extend machine life and guarantee long-lasting performance.

V O L V O